

SKU IC-18-B4-J1-QD

Job Name: Mark: Submitted By: Date: 05/19/2025


Non-oscillating Air Circulator, Product # IC-18-B4-J1-QD, 2900-4500 CFM



Model IC, non-oscillating circulator fans are designed for air movement in humid and demanding applications. Units are ideal for spot cooling and recirculating air in factories, warehouses, manufacturing facilities and garages. Mounting accessory sold separately.

- Totally enclosed motor
- Preassembled
- OSHA-compliant zinc plated wire guard

Certifications UL/cUL 507



s or ancillary products must be printed separa

Performance Characteristics

No Fan Curve Available.

Construction Features

Drive Type	Direct Drive	
Impeller Type	Propeller	
Impeller Material	Aluminum	
	Mounting hardware	
Includes	Power cord with 3-prong	
	plug	
Certifications	UL/cUL 507	
Required Accessory	Mounting accessory	

Motor Information

Motor Insulation	В	
Motor Phase	1	
Motor Type	NEMA	
Service Factor	1	
Voltage	115	
HP	1/4	
Hertz	60	
Motor Enclosure	Totally Enclosed Air Over	
RPM	1200	
Thermal Protection	AutoOverload	
Nominal Efficiency	64	
NEMA Frame Size	48	

Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)
1/4 0.00	0.00	750	<u>^</u>	CFM
	750	0	Sones	
1/4 0.00	1075	0	CFM	
			Sones	

California Residents



This product can expose you to chemicals including cadmium used in the processing of corrosion resistant metal and fasteners, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information visit www.P65Warnings.ca.gov